

Interference-based three-dimensional optical cold damping of a levitated nanoparticle

Youssef Ezzo ^{*}, Seyed Khalil Alavi ^{*,†} and Sungkun Hong [‡]

*Institute for Functional Matter and Quantum Technologies and
and Center for Integrated Quantum Science and Technology (IQST), University of Stuttgart, 70569 Stuttgart, Germany*



(Received 11 March 2026; accepted 14 July 2026; published 30 July 2026)

Achieving efficient three-dimensional feedback cooling of levitated nanoparticles is a key requirement for precision sensing and quantum control in levitated optomechanics. Here we demonstrate three-dimensional optical feedback cooling of a levitated nanoparticle using an interference-enhanced optical force generated within a single beam path. In this scheme, a weak auxiliary field copropagates with the trapping tweezer and interferes with it to produce a tunable optical force that enables cold damping along all three center-of-mass motional axes without additional beam paths or trap reconfiguration. Using this approach, we cool a 142-nm-diameter silica nanoparticle in high vacuum to effective temperatures of 625.8, 711.6, and 19.9 mK along the x , y , and z directions, respectively, at a pressure of 8.5×10^{-6} mbar. The cooling dynamics and their dependence on feedback gain and pressure are well described by a cold-damping model. Because the feedback force is generated optically, the scheme does not rely on electrical actuation and is directly compatible with neutral particles. These results establish interference-based optical forces as a simple and broadly applicable mechanism for three-dimensional feedback control in levitated optomechanics, with a clear pathway toward the quantum regime under improved vacuum and detection conditions.

DOI: [10.1103/63kt-tf4l](https://doi.org/10.1103/63kt-tf4l)

I. INTRODUCTION

Levitated optomechanics has emerged as a powerful platform to explore quantum behavior on the mesoscopic mass scale [1] and to develop ultrasensitive force and acceleration sensors [2–4]. Nanoparticles trapped by optical tweezers in high vacuum benefit from exceptional environmental isolation, allowing observation of quantum coherent motions even at room temperature [5,6]. A central requirement for these applications is efficient cooling of the particle's center-of-mass (CoM) motion, to stabilize the particle in high vacuum and to enable cooling toward the motional ground state.

Using cavity-assisted schemes, researchers have cooled motions of levitated particles to the quantum ground state, including both translational [7–9] and librational [10,11] modes. As a versatile cavity-free alternative, measurement-based feedback control has also been widely implemented, notably through electrically generated cold damping [12–14]. This approach has also enabled ground-state cooling of levitated nanoparticles [15,16]. However, the net charge required in such schemes can introduce excess decoherence and technical noise [17,18], motivating the development of purely optical feedback methods compatible with neutral particles.

Several optical cold-damping techniques have been demonstrated, including schemes based on scattering forces from single [19] or counterpropagating [20] beams, fast steering of the trapping beam [21], and frequency modulation of standing-wave traps [22], the latter recently achieving ground-state cooling. While these approaches have achieved remarkable performance, they typically rely on multiple optical delivery paths to the particle or specific beam geometries and are often restricted to cooling only selected motional directions. Such constraints can limit their flexibility, scalability, or simultaneous cooling of all motions.

Here, we present an interference-based optical cold-damping technique that enables simultaneous cooling of all three CoM motional degrees of freedom using a single copropagating auxiliary beam. The method relies on controlled interference between a primary optical tweezer and a weak auxiliary beam, generating a fully tunable optical force acting on the nanoparticle [23]. Using this method, we demonstrate three-dimensional cooling of a levitated nanoparticle to temperatures of 625.8, 711.6, and 19.9 mK along the x , y , and z axes, respectively, at a pressure of 8.5×10^{-6} mbar. The scheme is simple to implement and requires only single-axis optical delivery to the particle, providing a scalable route toward fully optical feedback control of neutral nanoparticles.

II. EXPERIMENTAL SETUP

As illustrated in Fig. 1, we trap a silica nanosphere (nominal diameter 142 nm) in high vacuum using an optical tweezer formed by tightly focusing a 1064 nm laser with an NA = 0.8 microscope objective. With 410 mW of optical power at the focus, the particle's CoM oscillation frequencies are $(\Omega_x, \Omega_y, \Omega_z)/2\pi \approx (315, 284, 83)$ kHz.

^{*}These authors contributed equally to this work.

[†]Contact author: skalavi@fmq.uni-stuttgart.de

[‡]Contact author: sungkun.hong@fmq.uni-stuttgart.de




FIG. 1. Experimental setup. A silica nanoparticle is trapped in high vacuum by a 1064 nm optical tweezer formed by NA = 0.8 objective. Backscattered light is collected by the same objective and routed via a Faraday rotator (FR) and a polarizing beam splitter (PBS) to the detection path, where balanced homodyne detection measures the axial (z) motion and split photodetectors measure the transverse (x, y) motions. An auxiliary beam derived at BS1 (an effective beam splitter with a variable splitting ratio) passes through a fiber-coupled amplitude modulator (AM) and a fiber stretcher (FS), and is then recombined with the trapping beam at BS2 to copropagate to the trap. A fiber polarization controller (FPC) is used to match the polarization of the auxiliary beam to that of the tweezer beam, maximizing the interference contrast after recombination. A slight displacement between the two beams gives rise to an interference-induced gradient force with nonzero components along all three spatial directions (inset). Feedback is implemented by electronically processing the measured motional signals with appropriate gains and delays and applying the resulting drive to the AM. A more detailed description of the setup is given in Appendix A.

The CoM motion is read out from the light backscattered by the particle. The backscattered field is collected by the same objective and routed to the detection optics via a Faraday rotator (FR) and a polarizing beam splitter (PBS). The detection path is split into two channels: a transverse readout that yields $x(t)$ and $y(t)$ via the split-detection scheme and an axial readout in which the $z(t)$ is measured by balanced homodyne detection. These signals are processed electronically and used to generate optical feedback forces.

In our implementation, the feedback force F_{fb} is realized via coherent interference between the primary tweezer field and a copropagating weak auxiliary field [23]. Their interference imposes an additional phase-dependent term on the optical potential, giving rise to a tunable force on top of the nominal tweezer forces. By introducing a small relative offset between the focal positions of the two beams, the force at the particle location can be engineered to have nonzero projections along x , y , and z (see Appendix B). Its amplitude scales as $F_{fb} \propto \sqrt{P_{tw} \cdot P_{aux}}$, where P_{tw} and P_{aux} denote the optical powers of the tweezer and auxiliary beams, respectively [23]. Feedback cooling is implemented by modulating P_{aux} in response to the measured motion such that the resulting force is approximately proportional to the particle velocity (see Appendix D), thereby providing damping of all CoM modes.

Experimentally, the auxiliary beam is derived from the main 1064 nm laser at BS1, which serves as an effective pick-off stage, and is sent through a fiber-coupled amplitude

modulator (AM), which provides fast control of P_{aux} . The measured signals $x(t)$, $y(t)$, and $z(t)$ are digitized and processed in real time using a field-programmable gate array (FPGA). In the FPGA, each signal is first passed through a digital bandpass filter centered at the corresponding mechanical resonance frequency, thereby isolating the particle motion signal from broadband noise. The filtered signals are then delayed by a quarter mechanical period ($\tau = \pi/2\Omega_0$) to approximate velocity-proportional signals. These phase-shifted signals are amplified, summed, and applied to the AM, realizing the three-dimensional (3D) viscous feedback force $F_{fb}(t)$.

A fiber stretcher (FS) in the auxiliary arm adjusts the optical path length and hence the phase of the auxiliary beam with respect to the primary tweezer field. We actively lock this phase by interfering a small fraction of the main field from the unused output port of BS2 with a power-matched portion of the auxiliary beam; the resulting error signal is fed back to the FS, achieving a fixed interference condition throughout the experiment.

III. EXPERIMENTAL RESULTS

The center-of-mass (CoM) motion of the trapped nanoparticle along each spatial direction $q \in \{x, y, z\}$ can be modeled as that of a damped harmonic oscillator subject to thermal noise and an externally applied feedback force. Its dynamics are described by the Langevin equation

$$m\ddot{q}(t) + m\Gamma_g\dot{q}(t) + m\Omega_0^2q(t) = F_{th}(t) + F_{fb}(t), \quad (1)$$

where m is the particle mass, Ω_0 is the mechanical resonance frequency, and Γ_g is the damping rate due to residual gas collisions. The thermal force $F_{th}(t)$ has zero mean and satisfies $\langle F_{th}(t)F_{th}(t') \rangle = 2m\Gamma_g k_B T \delta(t - t')$, where T is the bath temperature. As detailed in Appendix D, the cold-damping scheme is realized by applying a feedback force proportional to the measured particle displacement and delayed appropriately, such that $F_{fb}(t) \approx -m\Gamma_{fb}\dot{q}(t)$ [12,13]. Here, Γ_{fb} denotes the feedback-induced damping rate. This force increases the total effective damping to $\Gamma_{eff} = \Gamma_g + \Gamma_{fb}$, resulting in a reduction of the effective temperature of the CoM motion.

Following the cold-damping scheme with our interference-based optical force, we demonstrate cooling of the particle's motion. Figure 2(a) shows the measured power spectral densities (PSDs) of the z -axis motion for different feedback gains at a pressure of 2.3×10^{-5} mbar. We note that during the experiment, we also apply cooling of the transverse (x, y) motions with fixed gains to suppress any nonlinear intermodal couplings [15,16]. For each gain setting, the PSD is obtained by averaging 10 consecutive time traces of 1 s duration. The effective temperature is extracted by fitting the measured PSDs to the standard in-loop detection model [13,21,24], which accounts for feedback-induced correlation between detector noise and the particle (see Appendix E),

$$S_{xx}^L(\Omega) = \frac{(2k_B T \Gamma_g)/m}{(\Omega_0^2 - \Omega^2)^2 + \Omega^2 \Gamma_{eff}^2} + \frac{(\Omega_0^2 - \Omega^2)^2 + \Omega^2 \Gamma_g^2}{(\Omega_0^2 - \Omega^2)^2 + \Omega^2 \Gamma_{eff}^2} \sigma_N^2, \quad (2)$$




FIG. 2. (a) Power spectral densities (PSDs) of the particle motion along the z axis, measured at a pressure of 2.3×10^{-5} mbar for different feedback gains, corresponding to effective damping rates $\Gamma_{\text{eff}} \approx 0.16$ kHz (orange), 0.52 kHz (green), and 2.66 kHz (blue). Solid lines are fits to Eq. (2). (b) Extracted effective temperature T_{eff} of the z -axis motion as a function of Γ_{eff} . Each data point represents the mean of 10 independent measurements (1 s acquisition time each), with error bars indicating the standard deviation. The solid line shows the theoretical prediction based on Eq. (3), while the shaded region indicates the uncertainty due to the imprecision of the pressure gauge ($\approx 30\%$). The experimentally accessible feedback gain was limited by the saturation voltage of the amplitude modulator, preventing us from reaching the predicted optimum gain for the minimum T_{eff} .

where σ_N^2 denotes the displacement measurement noise floor. From the fitting results, the effective temperature T_{eff} is deduced (see Appendix E),

$$T_{\text{eff}} = T \frac{\Gamma_g}{\Gamma_{\text{eff}}} + \frac{m\Omega_0^2\Gamma_{\text{fb}}^2}{k_B\Gamma_{\text{eff}}}\sigma_N^2. \quad (3)$$

The first term in Eq. (3) corresponds to the familiar cold-damping result [25,26], where the effective temperature is reduced proportionally to the ratio $\Gamma_g/\Gamma_{\text{eff}}$. The second term arises from measurement noise fed back into the system and sets the ultimate limit to feedback cooling.

The extracted effective temperatures are shown in Fig. 2(b). Each data point denotes the mean T_{eff} , with error bars indicating the standard deviation. As expected, T_{eff} decreases with increasing feedback-induced damping rate Γ_{fb} . The solid curve in Fig. 2(b) is the prediction of Eq. (3), evaluated for $T = 300$ K with Γ_g estimated from kinetic theory in the rarefied-gas regime [27]. The excellent agreement between experiment and theory confirms that our cooling performance is well captured by the cold-damping model.

The effective temperature also depends on the background gas pressure, as the gas damping rate scales linearly with pressure, $\Gamma_g \propto p$. This behavior is summarized in Fig. 3, which shows the extracted effective temperatures as a function of pressure for the x , y , and z motions. For these measurements,




FIG. 3. Extracted effective temperatures T_{eff} of the particle motion along the x (red), y (green), and z (blue) axes as a function of background pressure. Each data point represents the mean temperature extracted from 12 consecutive PSDs, each calculated from a 50 ms time trace, with error bars indicating the standard deviation. As the pressure is reduced, T_{eff} decreases linearly (dashed lines), consistent with the expected pressure scaling of the gas damping rate. At lower pressures, deviations from linearity appear and T_{eff} saturates as the contribution of measurement noise [second term in Eq. (3)] becomes significant. Solid lines show the theoretical prediction based on Eq. (3), and the shaded regions indicate the uncertainty due to the pressure-gauge imprecision. The remaining deviations may arise from a slow drift of Γ_{fb} and/or a systematic calibration offset in the pressure gauge used to infer Γ_g .

the feedback gain is kept fixed as the pressure is varied. At higher effective temperatures, T_{eff} scales linearly with pressure, consistent with the expected pressure dependence of Γ_g . At lower effective temperatures, deviations from linearity, most notably for the transverse modes, appear as measurement noise becomes relevant and ultimately limits further cooling.

At a pressure of 8.5×10^{-6} mbar, we reach minimum effective temperatures of 625.8, 711.6, and 19.9 mK for the motions along x , y , and z , respectively. Figure 4 shows the corresponding PSDs of the cooled particle motions along all three axes. PSDs recorded without feedback at a pressure of 2 mbar are also shown for comparison. Along the axial direction, the cooled signal remains well above the detection noise floor (~ 1.9 pm/ $\sqrt{\text{Hz}}$), indicating that the cooling is predominantly limited by residual gas collisions rather than measurement noise. In contrast, the cooled transverse signals approach the detection limits of ~ 14.3 and ~ 26.5 pm/ $\sqrt{\text{Hz}}$ for the x and y axes, respectively, leaving only barely discernible resonance peaks.

IV. DISCUSSION AND CONCLUSION

In conclusion, we have demonstrated an interference-based optical cold-damping scheme using a copropagating auxiliary beam, which enables full three-dimensional cooling of a levitated nanoparticle. The method is simple to implement, and does not rely on multiple beam paths or complex




FIG. 4. PSDs of the particle motion along the x , y , and z axes, measured using split detections for the transverse directions (x , y) and homodyne detection for the axial direction (z). Each panel compares the PSDs measured without feedback cooling at a pressure of 2 mbar (red) and with simultaneous cooling of all three motions activated at a pressure of 8.6×10^{-6} mbar (blue). Feedback cooling strongly suppresses the mechanical resonances, leading to effective temperatures of 625.8, 711.6, 19.9 mK for the x , y , and z motions, respectively. For the transverse directions, the cooled resonances approach the detection noise floor. The resonance frequencies are indicated by arrows.

trap geometry. It is therefore readily compatible with a broad range of levitated optomechanical platforms, including microcavities [28,29], near-surface trapping architectures [30,31], and scalable multiparticle configurations [21]. These results establish interference-induced optical forces as a versatile tool for cooling and control in levitated optomechanics.

The prospect of ground-state cooling in the present scheme is currently limited by different mechanisms along different motional axes. Along the axial (z) direction, the minimum temperature is set by residual gas collisions, as evidenced by the observed linear pressure scaling of T_{eff} . Extrapolating this behavior indicates that the ground-state level, with mean occupation $\bar{n} = k_B T_{\text{eff}} / \hbar \Omega_0 \lesssim 1$, would become accessible at pressures of the order of 1×10^{-8} mbar [15,22], where the recoil heating dominates the decoherence process.

In contrast, the transverse (x , y) modes are already limited by detection noise at the lowest achieved pressures. In the present detection geometry, the displacement information for transverse motion is intrinsically limited since the scattered field carries maximal position information in directions perpendicular to the optical axis [32]. Collecting scattered light in a transverse direction, for example, using high-NA fiber-coupled microlenses [33], would substantially enhance the transverse displacement sensitivity and enable further cooling of the transverse modes.

ACKNOWLEDGMENTS

This research was funded by Deutsche Forschungsgemeinschaft (Project No. 523178467) and Carl-Zeiss-Stiftung (Johannes-Kepler Grant through IQST).

The authors declare no conflicts of interest.

DATA AVAILABILITY

The data that support the findings of this article are not publicly available. The data are available from the authors upon reasonable request.

APPENDIX A: EXPERIMENTAL APPARATUS

A schematic of the experimental setup is shown in Fig. 5. A collimated laser beam with $\lambda = 1064$ nm is tightly focused by a high-numerical-aperture microscope objective ($\text{NA} = 0.8$) to optically trap a silica nanoparticle (nominal diameter of 142 nm) inside a vacuum chamber. Light scattered by the particle in the backward direction is collected by the same objective and directed toward the detection system using a Faraday rotator (FR) followed by a polarizing beam splitter (PBS2).

In the detection path, a portion of the collected light is directed to a balanced homodyne detector at PBS3. The optical power sent to the homodyne arm is adjusted using half-wave plates ($\lambda/2$) placed before PBS3. The scattered field is fiber coupled and interfered with a strong local oscillator (LO) beam. To stabilize the relative phase between the signal and LO fields, the homodyne signal is processed by a Red Pitaya unit (RP3) and fed to a fiber stretcher (FS2). This configuration provides sensitive detection of the axial (z) motion.

The transmitted output of PBS3 is used for detection of the transverse (x and y) motions. This beam is split into two paths using a half-wave plate and PBS4, each directed to a split-detection module. In each module, a D-shaped mirror spatially divides the beam profile into two halves, converting transverse displacements into differential intensity signals that are measured with balanced photodetectors.

An auxiliary beam for generating feedback force is tapped by picking off a small fraction of the primary laser at PBS1 and coupling it into a fiber path containing an amplitude modulator (AM) and a fiber stretcher (FS1). A fiber polarization controller (FPC) is used to match the polarization to that of the primary beam. After the fiber, the auxiliary beam is recombined with the primary trapping beam at BS1 such that both beams propagate along the same beam path. Interference between the two fields at the trap location produces an additional optical force that is used for feedback cooling (see Appendix B for details).

To ensure stable operation of the interference-induced force, the relative optical phase between the primary and auxiliary beams is actively stabilized. Due to the extreme power disparity between the two beams, their direct superposition would completely wash out the interference fringes. To solve this, an error signal is generated by taking a heavily attenuated reflection of the primary beam from BS1 [using an optical density (OD) filter] and interfering it with a tapped-off portion of the auxiliary beam (taken at BS2 and recombined at BS3). This separate routing allows us to properly balance the optical powers of the two beams specifically for the phase-lock detector, yielding optimal interference contrast without affecting the power ratio sent to the optical trap. The interference signal is detected with a photodiode and processed by a Red Pitaya unit (RP1), which actuates FS1 to stabilize relative optical path-length fluctuations.




FIG. 5. Schematic of the experimental setup.

To generate the feedback force, the detected motion signals from the split and homodyne detectors are digitized and processed in real time using Red Pitaya units (RP2 and RP4). The processed signals are then summed and used to drive the amplitude modulator of the auxiliary beam, thereby producing a controlled optical force that simultaneously cools all the motions of the particle.

To provide further technical clarity and facilitate the reproduction of our experimental setup, we detail the specific models and suppliers of the key components and equipment used in our apparatus in Table I.

APPENDIX B: OPTICAL FORCE INDUCED BY TWO-BEAM INTERFERENCE

In this appendix, we analyze the optical force acting on a levitated nanoparticle arising from the interference between the copropagating tweezer field and a weak auxiliary field. Specifically, we consider the case in which the auxiliary beam is displaced relative to the tweezer field by an arbitrary vector, $\mathbf{r}_s = (x_s, y_s, z_s)$.

We model both fields as paraxial Gaussian beams propagating along the z axis. The main tweezer beam is centered at

the origin,

$$\mathcal{E}_{\text{tw}}(x, y, z) = \hat{x} E_{\text{tw}} A(x, y, z) e^{i\Phi(x, y, z)}, \quad (\text{B1})$$

where the three-dimensional amplitude envelope and the Gouy phase factor are given by $A(x, y, z) = \frac{w_0}{w(z)} \exp(-\frac{x^2+y^2}{w^2(z)})$ and $\Phi(x, y, z) = -[kz + \frac{k(x^2+y^2)}{2R(z)} - \psi(z)]$, respectively. The weak auxiliary beam is displaced by $\mathbf{r}_s$,

$$\mathcal{E}_{\text{aux}}(x, y, z) = \hat{x} E_s A(x - x_s, y - y_s, z - z_s) \times e^{i\Phi(x - x_s, y - y_s, z - z_s) + i\phi_s}. \quad (\text{B2})$$

The total optical intensity generated by the two fields is

$$I_{\text{tot}} = \frac{1}{2} c \epsilon_0 |\mathcal{E}_{\text{tw}} + \mathcal{E}_{\text{aux}}|^2 = \frac{1}{2} c \epsilon_0 [|\mathcal{E}_{\text{tw}}|^2 + 2 \cdot \text{Re}(\mathcal{E}_{\text{tw}} \cdot \mathcal{E}_{\text{aux}}^*) + |\mathcal{E}_{\text{aux}}|^2]. \quad (\text{B3})$$

The first term in Eq. (B3), $I_{\text{tw}} := \frac{1}{2} c \epsilon_0 |\mathcal{E}_{\text{tw}}|^2$, is the nominal optical intensity by the tweezer field. The second term [$I_{\text{intf}} := c \epsilon_0 \cdot \text{Re}(\mathcal{E}_{\text{tw}} \cdot \mathcal{E}_{\text{aux}}^*)$] represents the contribution arising from the interference between the two fields. The third term ($I_{\text{aux}} := \frac{1}{2} c \epsilon_0 |\mathcal{E}_{\text{aux}}|^2$) is the contribution of the auxiliary field in the absence of interference. We note that $|I_{\text{intf}}/I_{\text{aux}}| \sim$

TABLE I. Models and suppliers of the components and equipment used in the experimental setup.

Component	Supplier	Model / Series
Laser	Azurlight	ALS-IR-1064-20-E-CC-SF
Objective	Nikon	MUE12500
Signal processing board (RP)	Red Pitaya	STEMlab 125-14
Amplitude modulator (AM)	iXblue	NIR-MX-LN Series
Balanced Detectors (Homodyne and split)	Thorlabs	PDB425C
Photodetector (Phase lock)	Thorlabs	DET36A2
Fiber stretcher	PiezoDrive	FS-SM-SM980-5.8-125-N20-FC/APC-FC/APC
Faraday rotator	Coherent	110-21053-0003




FIG. 6. Simulated intensity distributions produced by two interfering, copropagating Gaussian beams at $\lambda = 1064$ nm: (a), (b) in the xy plane at axial position $z = 0$ nm and (c), (d) in the xz plane at lateral position $y = 0$ nm. The simulation assumes a tweezer power $P_{tw} = 414$ mW, an auxiliary-beam power $P_{aux} = 2.5$ μ W, the numerical aperture $NA = 0.8$, the relative optical phase $\phi_s = 84.7^\circ$, and an auxiliary-beam displacement $(x_s, y_s, z_s) = (500, 500, 10)$ nm. All panels are shown in $W\ m^{-2}$ on the same spatial scale; orange crosshairs indicate the intensity maxima. (a) Intensity of the primary trapping beam, I_{tw} , in the xy plane shows the characteristic Gaussian profile centered at $(x, y) = (0, 0)$. (b) Interference-induced term I_{intf} in the xy plane. Its maximum is significantly displaced from $(x, y) = (0, 0)$, resulting in a nonzero gradient at the trap center. The arrow at the center indicates the direction of the intensity gradient ∇I_{xy} at $(x, y) = (0, 0)$. (c) Intensity of the primary trapping beam, I_{tw} , in the xz plane, showing the expected Gaussian confinement at the focus $(x, z) = (0, 0)$ and characteristic diffraction-limited divergence along the propagation axis (z). (d) Interference-induced term I_{intf} in the xz plane. The asymmetric lobe structure along the z axis arises from a spatially varying phase difference between the two beams. The arrow at the center indicates the direction of the intensity gradient ∇I_{intf} at $(x, z) = (0, 0)$.

$|\mathcal{E}_{tw}/\mathcal{E}_{aux}| \gg 1$ [23]. Consequently, the dominant correction to the optical intensity, and hence to the optical potential $U_{tot} = -\alpha I_{tot}$ (α is the polarizability of the particle), introduced by the auxiliary field is the interference term (I_{intf}).

Figure 6 shows the simulated intensity distributions of the primary trapping beam and the weak auxiliary beam near the focus of the tweezer beam $[(x, y, z) = (0, 0, 0)]$. The displaced intensity extrema of I_{intf} both in the xy and xz planes indicate that by tuning the auxiliary beam's displacement and its optical phase relative to the tweezer beam, one can

generate an additional gradient force, $F_{intf} = -\alpha \nabla I_{intf}$, at the trap center with nonzero components along the x , y , and z axes.

APPENDIX C: PHASE STABILIZATION OF TWO BEAMS

The optical force used to cool the particle motion originates from the interference between the two beams and is therefore extremely sensitive to their relative phase (see Appendix B). This sensitivity can be verified by the measurement presented in Fig. 7. In this experiment, we cool the particle motion along




FIG. 7. Impact of phase stabilization on particle motion. (a) Evolution of the z -axis PSD as a function of time. The motion is stably cooled while the phase lock (PL) between the two beams is active ($t = 0$ to 7). When the PL is switched off at $t = 7$ s, random phase fluctuations occur, leading to unstable particle dynamics with the feedback force alternating between stochastic cooling and heating. (b) Selected PSDs of the z motion. When the PL is active (dark gray), the motion is stably cooled. When the PL is off, random phase drifts produce intervals of heating (light red) and cooling (light blue), depending on the instantaneous interference conditions. Measurements are performed at 0.1 mbar.

the z axis. The measurement is performed at a pressure of 0.1 mbar to prevent particle loss.

Figure 7(a) shows the power spectral density (PSD) of the z motion as a function of time, with each PSD computed from a time segment of 50 ms of the homodyne signal. At the start of the measurement, the phase lock between the two beams is active, producing stable cooling of the particle motion. At $t = 7$ s, the phase lock is turned off, leading to random relative phase fluctuations. Consequently, the particle dynamics become unstable and the cooling is ineffective, with the feedback force alternating between stochastic cooling and heating. Selected PSDs in Fig. 7(b) illustrate representative intervals of effective cooling and heating.

APPENDIX D: FEEDBACK COOLING THEORY

We model the nanoparticle's motion along a single axis $q(t)$ (with $q \in \{x, y, z\}$) as a damped harmonic oscillator subject to a stochastic thermal force $F_{\text{th}}(t)$ and an externally applied, tunable feedback force $F_{\text{fb}}(t)$,

$$m\ddot{q}(t) + m\Gamma_g\dot{q}(t) + m\Omega_0^2q(t) = F_{\text{th}}(t) + F_{\text{fb}}(t), \quad (\text{D1})$$

where Γ_g is the gas damping rate, m the particle mass, and Ω_0 the mechanical resonance frequency. The thermal force has zero mean and satisfies $\langle F_{\text{th}}(t)F_{\text{th}}(t') \rangle = 2m\Gamma_g k_B T \delta(t - t')$, with T the bath temperature.

To implement viscous feedback cooling, the applied force must be proportional to the particle's velocity such that $F_{\text{fb}}(t) = -m\Gamma_{\text{fb}}\dot{q}(t)$. Ideally, this force is generated from the time derivative of the measured displacement $q(t)$. In our experiment, however, we realize this term approximately by applying an appropriate time delay to the measured displacement signal. In the frequency domain, the Fourier transform of the velocity is given by $\mathcal{F}(\dot{q})(\Omega) = i\Omega\mathcal{F}(q)(\Omega)$, where $\mathcal{F}(q)$ denotes the Fourier transform of $q(t)$. For a harmonic oscillator, whose motion is strongly peaked around the reso-

nance frequency $\Omega = \Omega_0$, this relation can be approximated as $\mathcal{F}(\dot{q})(\Omega) \approx i\Omega_0\mathcal{F}(q)(\Omega)$. Taking the inverse Fourier transform then gives $\dot{q}(t) \approx -\Omega_0 \cdot q(t - \tau)$, where $\tau = \pi/(2\Omega_0)$.

We emphasize that the measured $q_{\text{meas}}(t)$ includes the detector noise $\xi(t)$, i.e., $q_{\text{meas}}(t) = q(t) + \xi(t)$. Hence, the feedback force also includes an additional term due to the noise,

$$F_{\text{fb}}(t) = m\Gamma_{\text{fb}}\Omega_0[q(t - \tau) + \xi(t - \tau)]. \quad (\text{D2})$$

By taking the Fourier transform of Eq. (D1), the power spectral density of $q(t)$ can be expressed as

$$S_{qq}(\Omega) = \frac{2k_B T \Gamma_g / m}{(\Omega_0^2 - \Omega^2)^2 + \Omega^2 \Gamma_{\text{eff}}^2} + \frac{\Omega_0^2 \Gamma_{\text{fb}}^2}{(\Omega_0^2 - \Omega^2)^2 + \Omega^2 \Gamma_{\text{eff}}^2} \sigma_N^2, \quad (\text{D3})$$

where $\Gamma_{\text{eff}} = \Gamma_g + \Gamma_{\text{fb}}$ is the total effective damping. The first term represents the thermodynamic cooling limit determined by the total effective damping, $\Gamma_{\text{eff}} = \Gamma_g + \Gamma_{\text{fb}}$. The second term describes noise-induced heating arising from the reinjection of measurement noise through the feedback loop. Here, the detector noise is assumed to be white, with a flat power spectral density given by $S_{nn}(\Omega) = \sigma_N^2$.

The effective center-of-mass temperature T_{eff} is determined from the variance of the physical motion $\langle q^2 \rangle$, using the equipartition theorem, which relates the mean potential energy of the particle to T_{eff} as

$$E_{\text{pot}} = \frac{1}{2}m\Omega_0^2\langle q^2 \rangle = \frac{1}{2}k_B T_{\text{eff}}. \quad (\text{D4})$$

Parseval's theorem allows us to express this position variance as the integral of the PSD, $S_{qq}(\Omega)$:

$$\langle q^2 \rangle = \frac{1}{2\pi} \int_{-\infty}^{\infty} S_{qq}(\Omega) d\Omega. \quad (\text{D5})$$

Evaluating the integral analytically yields

$$T_{\text{eff}} = \frac{m\Omega_0^2}{2k_B} \left(\frac{2k_B T \Gamma_g}{m\Omega_0^2 \Gamma_{\text{eff}}} + \frac{(\Gamma_{\text{eff}} - \Gamma_g)^2}{\Gamma_{\text{eff}}} \sigma_N^2 \right). \quad (\text{D6})$$

APPENDIX E: CALIBRATION AND TEMPERATURE EXTRACTION

The particle's motion is monitored with a balanced photodetector, which outputs a voltage signal $v_q(t)$ proportional to the displacement $q(t)$. We convert $v_q(t)$ to $q(t)$ using a linear calibration factor c_{cal} .

To determine c_{cal} , we record voltage time traces under calibration conditions at moderate pressure ($p \approx 2$ mbar) with feedback disabled. In this regime, the particle behaves as a thermal harmonic oscillator in equilibrium with a bath at $T \approx 300$ K. We extract the voltage variance $\langle v_q^2 \rangle$ by fitting the measured PSD of the calibration data to a Lorentzian and integrating the fitted spectrum. The calibration factor then follows from the equipartition theorem,

$$\frac{1}{2} m \Omega_0^2 \langle q^2 \rangle = \frac{1}{2} m \Omega_0^2 \frac{\langle v_q^2 \rangle}{c_{\text{cal}}^2} = \frac{1}{2} k_B T. \quad (\text{E1})$$

Solving for c_{cal} yields $c_{\text{cal}} = \sqrt{m \Omega_0^2 \langle v_q^2 \rangle / (k_B T)}$. Experimental PSDs recorded in units of V^2/Hz can now be converted to the PSDs regarding the particle's displacements in units of m^2/Hz .

We emphasize that to infer $S_{qq}(\Omega)$, we do not use a separate detector located outside the feedback loop. Instead, we use the same detector that provides the signal for feedback (*in-loop detection*). In such a configuration, the measurement contains an additional contribution arising from the interference between the detector noise $\xi(t)$ and the system response driven by the reinjection of $\xi(t)$ through the feedback loop. The resulting PSD of the measured signal $S_{qq}^{\text{IL}}(\Omega)$ is given by [13]

$$S_{qq}^{\text{IL}}(\Omega) = \frac{2k_B T \Gamma_g / m}{(\Omega_0^2 - \Omega^2)^2 + \Omega^2 \Gamma_{\text{eff}}^2} + \frac{(\Omega_0^2 - \Omega^2)^2 + \Omega^2 \Gamma_g^2}{(\Omega_0^2 - \Omega^2)^2 + \Omega^2 \Gamma_{\text{eff}}^2} \sigma_N^2. \quad (\text{E2})$$

The difference in the second term compared with Eq. (D3) reflects the characteristic *noise squashing* associated with in-loop detection. Despite this distortion, we can still estimate the effective temperature as follows. We first fit the measured spectra to Eq. (E2), thus obtaining the parameters needed to infer T_{eff} using Eq. (D6).




FIG. 8. Extended frequency spectrum of the z -axis motion under varying feedback gains at a pressure of 2.3×10^{-5} mbar (corresponding to Fig. 2 in the main text). The signal clearly resolves the mechanical resonance before flattening out to the homodyne detection noise floor. No spurious technical noise is observed near the mechanical resonance band.

In the fitting routine, we treat Γ_{eff} , Γ_g , and Ω_0 as free parameters. The remaining quantities are determined independently: the detection noise floor σ_N^2 is estimated from the high-frequency background, the particle mass m is determined from the nominal particle specification (density 1850 kg/m^3 , diameter 142 nm) provided by the vendor (microParticles GmbH), and the bath temperature is assumed to be $T = 300 \text{ K}$.

APPENDIX F: WIDE-SPAN POWER SPECTRAL DENSITY

To verify the integrity of the detection signal and characterize the measurement background, we present a set of PSDs that we show in the main text over an extended frequency range. This wide-span spectrum corresponds directly to the data shown in Fig. 2 of the main text. As shown in Fig. 8, the spectrum flattens to a constant noise floor away from the mechanical resonance band. Importantly, no spurious technical noise peaks are observed near the mechanical resonance. We determine the value of σ_N^2 by integrating the noise-floor level in a high-frequency band, for example from 460 to 480 kHz.

- [1] C. Gonzalez-Ballester, M. Aspelmeyer, L. Novotny, R. Quidant, and O. Romero-Isart, Levitodynamics: Levitation and control of microscopic objects in vacuum, *Science* **374**, eabg3027 (2021).
- [2] G. Ranjit, M. Cunningham, K. Casey, and A. A. Geraci, Zep-tonewton force sensing with nanospheres in an optical lattice, *Phys. Rev. A* **93**, 053801 (2016).
- [3] F. Monteiro, W. Li, G. Afek, C. L. Li, M. Mossman, and D. C. Moore, Force and acceleration sensing with optically levitated

nanogram masses at microkelvin temperatures, *Phys. Rev. A* **101**, 053835 (2020).

- [4] D. C. Moore and A. A. Geraci, Searching for new physics using optically levitated sensors, *Quantum Sci. Technol.* **6**, 014008 (2021).
- [5] D. E. Chang, C. A. Regal, S. B. Papp, D. J. Wilson, J. Ye, O. Painter, H. J. Kimble, and P. Zoller, Cavity opto-mechanics using an optically levitated nanosphere, *Proc. Natl. Acad. Sci. USA* **107**, 1005 (2010).

- [6] O. Romero-Isart, M. L. Juan, R. Quidant, and J. I. Cirac, Toward quantum superposition of living organisms, *New J. Phys.* **12**, 033015 (2010).
- [7] U. Delić, M. Reisenbauer, K. Dare, D. Grass, V. Vuletić, N. Kiesel, and M. Aspelmeyer, Cooling of a levitated nanoparticle to the motional quantum ground state, *Science* **367**, 892 (2020).
- [8] A. Ranfagni, K. Børkje, F. Marino, and F. Marin, Two-dimensional quantum motion of a levitated nanosphere, *Phys. Rev. Res.* **4**, 033051 (2022).
- [9] J. Piotrowski, D. Windey, J. Vijayan, C. Gonzalez-Ballester, A. de los Ríos Sommer, N. Meyer, R. Quidant, O. Romero-Isart, R. Reimann, and L. Novotny, Simultaneous ground-state cooling of two mechanical modes of a levitated nanoparticle, *Nat. Phys.* **19**, 1009 (2023).
- [10] L. Dania, O. S. Kremer, J. Piotrowski, D. Candoli, J. Vijayan, O. Romero-Isart, C. Gonzalez-Ballester, L. Novotny, and M. Frimmer, High-purity quantum optomechanics at room temperature, *Nat. Phys.* **21**, 1603 (2025).
- [11] S. Troyer, F. Fechtel, L. Hummer, H. Rudolph, B. A. Stickler, U. Delić, and M. Arndt, Quantum ground-state cooling of two librational modes of a nanorotor *Nat. Phys.* **22**, 584 (2026).
- [12] F. Tebbenjohanns, M. Frimmer, A. Militaru, V. Jain, and L. Novotny, Cold damping of an optically levitated nanoparticle to microkelvin temperatures, *Phys. Rev. Lett.* **122**, 223601 (2019).
- [13] G. P. Conangla, F. Ricci, M. T. Cuairan, A. W. Schell, N. Meyer, and R. Quidant, Optimal feedback cooling of a charged levitated nanoparticle with adaptive control, *Phys. Rev. Lett.* **122**, 223602 (2019).
- [14] O. Kremer, I. Califrer, D. Tandeitnik, J. P. von der Weid, G. Temporão, and T. Guerreiro, All-electrical cooling of an optically levitated nanoparticle, *Phys. Rev. Appl.* **22**, 024010 (2024).
- [15] L. Magrini, P. Rosenzweig, C. Bach, A. Deutschmann-Olek, S. G. Hofer, S. Hong, N. Kiesel, A. Kugi, and M. Aspelmeyer, Real-time optimal quantum control of mechanical motion at room temperature, *Nature (London)* **595**, 373 (2021).
- [16] F. Tebbenjohanns, M. L. Mattana, M. Rossi, M. Frimmer, and L. Novotny, Quantum control of a nanoparticle optically levitated in cryogenic free space, *Nature (London)* **595**, 378 (2021).
- [17] E. Hebestreit, M. Frimmer, R. Reimann, and L. Novotny, Sensing static forces with free-falling nanoparticles, *Phys. Rev. Lett.* **121**, 063602 (2018).
- [18] M. Kamba, N. Hara, and K. Aikawa, Quantum squeezing of a levitated nanomechanical oscillator, *Science* **389**, 1225 (2025).
- [19] L. Dania, D. S. Bykov, M. Knoll, P. Mestres, and T. E. Northup, Optical and electrical feedback cooling of a silica nanoparticle levitated in a Paul trap, *Phys. Rev. Res.* **3**, 013018 (2021).
- [20] T. Li, S. Kheifets, and M. G. Raizen, Millikelvin cooling of an optically trapped microsphere in vacuum, *Nat. Phys.* **7**, 527 (2011).
- [21] J. Vijayan, Z. Zhang, J. Piotrowski, D. Windey, F. van der Laan, M. Frimmer, and L. Novotny, Scalable all-optical cold damping of levitated nanoparticles, *Nat. Nanotechnol.* **18**, 49 (2023).
- [22] M. Kamba, R. Shimizu, and K. Aikawa, Optical cold damping of neutral nanoparticles near the ground state in an optical lattice, *Opt. Express* **30**, 26716 (2022).
- [23] S. K. Alavi, Y. Ezzo, A. Pulikkathara, and S. Hong, Interference-enhanced optical force by weak light fields on a levitated nanoparticle, *Opt. Express* **33**, 40384 (2025).
- [24] B. Melo, M. T. Cuairan, G. F. M. Tomassi, N. Meyer, and R. Quidant, Vacuum levitation and motion control on chip, *Nat. Nanotechnol.* **19**, 1270 (2024).
- [25] P. F. Cohadon, A. Heidmann, and M. Pinard, Cooling of a mirror by radiation pressure, *Phys. Rev. Lett.* **83**, 3174 (1999).
- [26] M. Poggio, C. L. Degen, H. J. Mamin, and D. Rugar, Feedback Cooling of a Cantilever's Fundamental Mode below 5 mK, *Phys. Rev. Lett.* **99**, 017201 (2007).
- [27] S. A. Beresnev, V. G. Chernyak, and G. A. Fomyagin, Motion of a spherical particle in a rarefied gas. part 2. drag and thermal polarization, *J. Fluid Mech.* **219**, 405 (1990).
- [28] L. Magrini, R. A. Norte, R. Riedinger, I. Marinković, D. Grass, U. Delić, S. Gröblacher, S. Hong, and M. Aspelmeyer, Near-field coupling of a levitated nanoparticle to a photonic crystal cavity, *Optica* **5**, 1597 (2018).
- [29] S. K. Alavi, Z. Sheng, H. Lee, H. Lee, and S. Hong, Enhanced optomechanical coupling between an optically levitated particle and an ultrahigh-Q optical microcavity, *ACS Photon.* **12**, 34 (2025).
- [30] R. Diehl, E. Hebestreit, R. Reimann, F. Tebbenjohanns, M. Frimmer, and L. Novotny, Optical levitation and feedback cooling of a nanoparticle at subwavelength distances from a membrane, *Phys. Rev. A* **98**, 013851 (2018).
- [31] P. Ju, Y. Jin, K. Shen, Y. Duan, Z. Xu, X. Gao, X. Ni, and T. Li, Near-field GHz rotation and sensing with an optically levitated nanodumbbell, *Nano Lett.* **23**, 10157 (2023).
- [32] F. Tebbenjohanns, M. Frimmer, and L. Novotny, Optimal position detection of a dipolar scatterer in a focused field, *Phys. Rev. A* **100**, 043821 (2019).
- [33] S. K. Alavi, J. M. M. Romero, P. Ruchka, S. Jakovljević, H. Giessen, and S. Hong, Compact vacuum levitation and control platform with a single 3D-printed fiber lens, *Photon. Res.* **14**, 201 (2026).